

**PRIMA** BS24.K1.P24.XY

**Type:** ceiling and wall lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Light body:** painted aluminium RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) or RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
18,1	3000	2378	1593	240	110	M	O*	-	Q*	-	1900

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 18,1 W

**Color temperature:** 3000 K

**Module luminous flux:** 2378 lm

**Luminaire luminous flux:** 1593 lm

**A:** 240 mm

**B:** 110 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Not available

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 1900 g

Lucis BS24.K1.P24.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS24.K1.P24.X PRIMA LED  
Lamps: 1 x LED G5

