


PRIMA BS24.K2.P24.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) or RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
18,1	4000	2491	1669	240	110	M	O*	-	Q*	-	1900

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 18,1 W

Color temperature: 4000 K

Module luminous flux: 2491 lm

Luminaire luminous flux: 1669 lm

A: 240 mm

B: 110 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1900 g

Lucis BS24.K2.P24.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS24.K2.P24.X PRIMA LED
Lamps: 1 x LED G5

