

PRIMA BS34.K3.P34.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) or RAL Brass (.74)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	DALI 2	Hand icon	Person icon	Bluetooth	Emergency	Weight
23,3	3000	3052	2045	340	120	M	O*	P*	Q*	-	2500

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 23,3 W

Color temperature: 3000 K

Module luminous flux: 3052 lm

Luminaire luminous flux: 2045 lm

A: 340 mm

B: 120 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2500 g

Lucis BS34.K3.P34.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS34.K3.P34.X PRIMA LED
Lamps: 1 x LED G5

