


PRIMA BS44.K2.P44.XY

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: painted aluminium RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) or RAL Brass (.74)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | DALI 2 | 0* | P* | Q* | - | - | 4400 |
|------|------|-------------------------|----------------------------|-----|-----|--------|----|----|----|---|---|------|
| 44,5 | 4000 | 6087 | 4078 | 440 | 130 | M | O* | P* | Q* | - | - | 4400 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 44,5 W

Color temperature: 4000 K

Module luminous flux: 6087 lm

Luminaire luminous flux: 4078 lm

A: 440 mm

B: 130 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 4400 g

Lucis BS44.K2.P44.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS44.K2.P44.X PRIMA LED
Lamps: 1 x LED G5

