


PRIMA BS44.K3.P44.XY

Type: luminaire de plafond et mural

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: aluminium laqué RAL 9016 (.41), RAL 9005 (.45), RAL Argento dorato (.70), RAL Bronze (.73) ou RAL Laiton (.74)



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | DALI 2 | Emergency | Bluetooth | Track system | Sádrokarton | Weight | |
|----|------|-------------------------------|----------------------------------|-----|-----|-----------|-----------|-----------|--------------|-------------|--------|------|
| 29 | 3000 | 3945 | 2643 | 440 | 130 | M | O* | P* | Q* | - | - | 4400 |

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 29 W

Température Couleur: 3000 K

Module luminous flux: 3945 lm

Luminaire luminous flux: 2643 lm

A: 440 mm

B: 130 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 4400 g

Lucis BS44.K3.P44.X PRIMA LED / LDC (Polar)

Luminaire: Lucis BS44.K3.P44.X PRIMA LED
Lamps: 1 x LED G5

