



OMNIA LR2.K1.02.X

Typ: Stehleuchte

Lampenschirm: Acrylglas

Metallteile: lackiertes Stahlblech RAL 9003 (.60), RAL 9005 (.61) oder RAL 7016 (.62)



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☰	☒	☒	☒	☒	☒
19,2	3000	2474	1920	680	370	1700	1250	-	-	-	-	-	-	12200

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 19,2 W

Farbtemperatur: 3000 K

Module luminous flux: 2474 lm

Luminaire luminous flux: 1920 lm

A: 680 mm

B: 370 mm

C: 1700 mm

D: 1250 mm

Dali 2: Nicht Verfügbar

Bewegungsmelder: Nicht Verfügbar

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Nicht Verfügbar

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Lucis LR2.K1.O2.X_pc(2) OMNIA LED / LDC (Polar)

Luminaire: Lucis LR2.K1.O2.X_pc(2) OMNIA LED
Lamps: 1 x LED G5

