


OMNIA ZT2.12.K2.O2.XY

Type: suspension lamp

Lampshade: acrylic glass

Metal parts: painted steel plate RAL 9003 (.60), RAL 9005 (.61) or RAL 7016 (.62)

Pendant: rod



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | C | DALI 2 | Motion sensor | Bluetooth | Track system | Weight |
|------|------|-------------------------------|----------------------------------|-----|-----|-----------|------------------|-----------|-----------------|--------|
| 13,4 | 4000 | 1930 | 1499 | 605 | 420 | M | - | - | Q* | 5000 |

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 13,4 W

Color temperature: 4000 K

Module luminous flux: 1930 lm

Luminaire luminous flux: 1499 lm

A: 605 mm

C: 420 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 5000 g

Lucis ZT2.12.K2.O2.X_pc(2) OMNIA LED / LDC (Polar)

Luminaire: Lucis ZT2.12.K2.O2.X_pc(2) OMNIA LED
Lamps: 1 x LED G5

