



IZAR C ZL4.IC.K1.440.91Y

- Type:** suspension lamp
- Lampshade:** acrylic glass
- Light body:** white painted steel plate
- Pendant:** steel wire suspension with a transparent cable



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | ⚡ | 🚶 | 🚶 | 📶 | 📄 | 👤 |
|------|------|-------------------------|----------------------------|-----|-----|------|-----|--------|---|----|----|---|---|------|
| 37,7 | 3000 | 4448 | 3 696 | 440 | 440 | 2000 | 440 | M | - | P* | Q* | - | - | 8000 |

- Voltage:** 230V
- IK code:** IK06
- Ballast:** Driver
- CRI:** >90
- LED life:** L80/F10 50000 hours
- Watt:** 37,7 W
- Color temperature:** 3000 K
- Module luminous flux:** 4448 lm
- Luminaire luminous flux:** 3 696 lm
- A:** 440 mm
- B:** 440 mm
- C:** 2000 mm
- D:** 440 mm
- Dali 2:** Available
- Motion sensor:** Not available
- Emergency module:** Available on inquiry
- Bluetooth control:** Available on inquiry
- Track system:** Not available
- Sádrokarton:** Not available
- Weight:** 8000 g

Lucis ZL4.IC.K1.440.X IZAR C LED / LDC (Polar)

Luminaire: Lucis ZL4.IC.K1.440.X IZAR C LED
Lamps: 1 x LED 252/160-G5

