


IZAR C ZL4.IC.K2.600.91Y

- Type:** suspension lamp
- Lampshade:** acrylic glass
- Light body:** white painted steel plate
- Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	D	DALI 2	☺	☺	☺	☺	☺	☺
46,1	4000	6087	5052	600	600	2000	600	M	-	P*	Q*	-	-	14400

- Voltage:** 230V
- IK code:** IK06
- Ballast:** Driver
- CRI:** >90
- LED life:** L80/F10 50000 hours
- Watt:** 46,1 W
- Color temperature:** 4000 K
- Module luminous flux:** 6087 lm
- Luminaire luminous flux:** 5052 lm
- A:** 600 mm
- B:** 600 mm
- C:** 2000 mm
- D:** 600 mm
- Dali 2:** Available
- Motion sensor:** Not available
- Emergency module:** Available on inquiry
- Bluetooth control:** Available on inquiry
- Track system:** Not available
- Sádrokarton:** Not available
- Weight:** 14400 g

Lucis ZL4.IC.K2.600.X IZAR C LED / LDC (Polar)

Luminaire: Lucis ZL4.IC.K2.600.X IZAR C LED
Lamps: 1 x LED 340/200-G5

