

POLARIS ZT PE ZT.P1.600.XY PE



Type: suspension lamp

Lampshade: polyethylene opal PE

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: rod

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
48,5	3000	7216	6639	600	1000	M	-	P*	Q*	R*	8900

Voltage: 230V

Ballast: Driver

IK code: IK10

CRI: >90

LED life: L80/F10 50000 hours

Watt: 48,5 W

Color temperature: 3000 K

Module luminous flux: 7216 lm

Luminaire luminous flux: 6639 lm

A: 600 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8900 g

Lucis ZT.P1.600.X PE POLARIS ZT PE LED / LDC (Polar)

Luminaire: Lucis ZT.P1.600.X PE POLARIS ZT PE LED
Lamps: 1 x LED G6

