

POLARIS ZL PE ZL1.P2.600.XY PE



Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

Suspension: câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	☼	☼	Bluetooth	☰	📖	
48,5	4000	7800	7176	600	2000	M	-	P*	Q*	R*	-	8700

Tension: 230V

Ballaste: Driver

IK code: IK10

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 48,5 W

Température Couleur: 4000 K

Module luminous flux: 7800 lm

Luminaire luminous flux: 7176 lm

A: 600 mm

C: 2000 mm

Dali 2: Disponible

Capteur de mouvement: Disponible

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Disponible sur demande

Sádrokarton: Non disponible

Poids: 8700 g

Lucis ZL1.P2.600.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.600.X PE POLARIS ZL PE LED
Lamps: 1 x LED G6

