


CAPELLA S24.L1.R4.Y

Type: luminaire plafonnier

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: tôle en acier peint en blanc

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	☒	☒	☒	☒	☒	☒	☒
16,2	3000	2372	1405	280	240	210	M	O*	-	Q*	-	-	-	2900

Lucis S24.L1.R4 CAPELLA LED / LDC (Polar)

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 16,2 W

Température Couleur: 3000 K

Module luminous flux: 2372 lm

Luminaire luminous flux: 1405 lm

A: 280 mm

B: 240 mm

C: 210 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2900 g

Luminaire: Lucis S24.L1.R4 CAPELLA LED
Lamps: 1 x LED G6

