



CAPELLA S24.L2.R4.Y

**Type:** luminaire plafonnier

**Abat-jour:** verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

**Luminaire:** tôle en acier peint en blanc

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	☒	☒	☒	☒	☒	☒	☒
16,2	4000	2564	1570	280	240	210	M	O*	-	Q*	-	-	-	2900

Lucis S24.L2.R4 CAPELLA LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK01

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 16,2 W

**Température Couleur:** 4000 K

**Module luminous flux:** 2564 lm

**Luminaire luminous flux:** 1570 lm

**A:** 280 mm

**B:** 240 mm

**C:** 210 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible sur demande

**Module d'urgence:** Non disponible

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 2900 g

Luminaire: Lucis S24.L2.R4 CAPELLA LED  
Lamps: 1 x LED G6

