


FORUM PE ZL3.K1.050.Y PE

**Type:** suspension lamp

**Lampshade:** polyethylene opal PE

**Metal parts:** painted steel plate RAL 9006 structured

**Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK10	IP20	Bluetooth	Emergency	Weight
44,5	3000	5810	5340	500	90	2000	M	-	P*	Q*	-	4200

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 44,5 W

**Color temperature:** 3000 K

**Module luminous flux:** 5810 lm

**Luminaire luminous flux:** 5340 lm

**A:** 500 mm

**B:** 90 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 4200 g

Lucis ZL3.K1.050 PE FORUM PE LED / LDC (Polar)

Luminaire: Lucis ZL3.K1.050 PE FORUM PE LED  
Lamps: 1 x LED G5

