


FORUM PE ZL3.K2.O60.Y PE

**Type:** suspension lamp

**Lampshade:** polyethylene opal PE

**Metal parts:** painted steel plate RAL 9006 structured

**Pendant:** steel wire suspension with a transparent cable



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight	
50,8	4000	6975	6411	600	100	2000	M	-	P*	Q*	-	5300

**Voltage:** 230V

**Ballast:** Driver

**IK code:** IK10

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 50,8 W

**Color temperature:** 4000 K

**Module luminous flux:** 6975 lm

**Luminaire luminous flux:** 6411 lm

**A:** 600 mm

**B:** 100 mm

**C:** 2000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 5300 g

Lucis ZL3.K2.O60 PE FORUM PE LED / LDC (Polar)

Luminaire: Lucis ZL3.K2.O60 PE FORUM PE LED  
Lamps: 1 x LED G5

