


IZAR I I1.L1.900.XY

Type: wall lamp

Lampshade: acrylic glass in combination with acrylic glass white (.92), black (.93) or stainless steel (.83)

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | IP 20 | LED | CRI >90 | Weight | |
|------|------|-------------------------|----------------------------|-----|----|----|--------|-------|-----|---------|--------|------|
| 30,7 | 3000 | 4047 | 3345 | 900 | 80 | 40 | M | - | - | Q* | - | 2000 |

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 30,7 W

Color temperature: 3000 K

Module luminous flux: 4047 lm

Luminaire luminous flux: 3345 lm

A: 900 mm

B: 80 mm

C: 40 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2000 g

Lucis I1.L1.900.X IZAR I LED / LDC (Polar)

Luminaire: Lucis I1.L1.900.X IZAR I LED
Lamps: 1 x LED G6

