


CHARON PMMA S26.L1.CA2.Y

Typ: Decken- und Wandleuchte

Lampenschirm: Acrylglas PMMA

Leuchte: weiß lackiertes Stahlblech



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Exit	Bluetooth	Track	Weight
16,2	3000	2372	1554	300	260	115	M	O*	-	Q*	-	1200

Spannung: 230V

IK Code: IK06

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 16,2 W

Farbtemperatur: 3000 K

Module luminous flux: 2372 lm

Luminaire luminous flux: 1554 lm

A: 300 mm

B: 260 mm

C: 115 mm

Dali 2: Verfügbar

Bewegungsmelder: Verfügbar auf Anfrage

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Verfügbar auf Anfrage

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 1200 g

Lucis S26.L1.CA2 CHARON PMMA LED / LDC (Polar)

Luminaire: Lucis S26.L1.CA2 CHARON PMMA LED
Lamps: 1 x LED G6

