



CHARON PMMA S26.L1.CA2.Y

Type: ceiling and wall lamp

Lampshade: acrylic glass PMMA

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|-----|--------|---------------|------------------|-----------|--------------|--------|
| 16,2 | 3000 | 2372 | 1554 | 300 | 260 | 115 | M | O* | - | Q* | - | 1200 |

Lucis S26.L1.CA2 CHARON PMMA LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16,2 W

Color temperature: 3000 K

Module luminous flux: 2372 lm

Luminaire luminous flux: 1554 lm

A: 300 mm

B: 260 mm

C: 115 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1200 g

Luminaire: Lucis S26.L1.CA2 CHARON PMMA LED
Lamps: 1 x LED G6

