




CHARON PMMA S26.L1.CA2.Y

**Type:** luminaire de plafond et mural  
**Abat-jour:** verre acrylique PMMA  
**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight
16,2	3000	2372	1554	300	260	115	M	O*	-	Q*	1200

Lucis S26.L1.CA2 CHARON PMMA LED / LDC (Polar)

**Tension:** 230V  
**IK code:** IK06  
**Ballaste:** Driver  
**CRI:** >90  
**La vie de LED:** L80/F10 50000 heures  
**Watt:** 16,2 W  
**Température Couleur:** 3000 K  
**Module luminous flux:** 2372 lm  
**Luminaire luminous flux:** 1554 lm  
**A:** 300 mm  
**B:** 260 mm  
**C:** 115 mm  
**Dali 2:** Disponible  
**Capteur de mouvement:** Disponible sur demande  
**Module d'urgence:** Non disponible  
**Contrôle Bluetooth:** Disponible sur demande  
**Track system:** Non disponible  
**Sádrokarton:** Non disponible  
**Poids:** 1200 g

Luminaire: Lucis S26.L1.CA2 CHARON PMMA LED  
 Lamps: 1 x LED G6

