



CHARON PMMA S44.L1.CA4.Y

**Type:** luminaire de plafond et mural

**Abat-jour:** verre acrylique PMMA

**Luminaire:** tôle en acier peint en blanc



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Exit	Bluetooth	Track system	Weight
37,1	3000	5628	4113	480	440	160	M	O*	P*	Q*	-	2600

Lucis S44.L1.CA4 CHARON PMMA LED / LDC (Polar)

**Tension:** 230V

**IK code:** IK06

**Ballaste:** Driver

**CRI:** >90

**La vie de LED:** L80/F10 50000 heures

**Watt:** 37,1 W

**Température Couleur:** 3000 K

**Module luminous flux:** 5628 lm

**Luminaire luminous flux:** 4113 lm

**A:** 480 mm

**B:** 440 mm

**C:** 160 mm

**Dali 2:** Disponible

**Capteur de mouvement:** Disponible sur demande

**Module d'urgence:** Disponible sur demande

**Contrôle Bluetooth:** Disponible sur demande

**Track system:** Non disponible

**Sádrokarton:** Non disponible

**Poids:** 2600 g

Luminaire: Lucis S44.L1.CA4 CHARON PMMA LED  
Lamps: 1 x LED G6

