



CHARON PMMA S56.L1.CA6.Y

**Type:** ceiling and wall lamp

**Lampshade:** acrylic glass PMMA

**Light body:** white painted steel plate



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency module	Bluetooth	Track system	Weight
42,7	3000	6432	4632	600	560	175	M	O*	P*	Q*	-	4000

Lucis S56.L1.CA6 CHARON PMMA LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK06

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 42,7 W

**Color temperature:** 3000 K

**Module luminous flux:** 6432 lm

**Luminaire luminous flux:** 4632 lm

**A:** 600 mm

**B:** 560 mm

**C:** 175 mm

**Dali 2:** Available

**Motion sensor:** Available on inquiry

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Not available

**Sádrokarton:** Not available

**Weight:** 4000 g

Luminaire: Lucis S56.L1.CA6 CHARON PMMA LED  
Lamps: 1 x LED G6

