




CHARON IP44 PS24.L2.T12.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Bluetooth	Emergency	Weight
10,7	4000	1738	1182	280	240	125 Project 1	M	O*	-	0*	1800 g

Operator
Telephone
Fax
e-Mail

DIALUX
11.03.2024

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 10,7 W

Color temperature: 4000 K

Module luminous flux: 1738 lm

Luminaire luminous flux: 1182 lm

A: 280 mm

B: 240 mm

C: 125 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 1800 g

Lucis PS24.L2.T12 CHARON LED / LDC (Polar)

Luminaire: Lucis PS24.L2.T12 CHARON LED
Lamps: 1 x LED G6

