




CHARON IP44 PS29.L1.T135.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Motion sensor	Emergency	Bluetooth	Track system	Weight
16	3000	2412	1640	360	290	130 Project 1	M	O*	-	O*	-	2900 g

Operator
Telephone
Fax
e-Mail

DIALUX
11.03.2024

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 16 W

Color temperature: 3000 K

Module luminous flux: 2412 lm

Luminaire luminous flux: 1640 lm

A: 360 mm

B: 290 mm

C: 130 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Not available

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2900 g

Lucis PS29.L1.T135 CHARON LED / LDC (Polar)

Luminaire: Lucis PS29.L1.T135 CHARON LED
Lamps: 1 x LED G6

