


CHARON S24.L2.T12.Y

Type: luminaire de plafond et mural

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: tôle en acier peint en blanc

Could be combined with metal ring in white, chrome, brass or stainless steel.



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Bluetooth	Track system	Weight	
16,2	4000	2564	1764	280	240	125	M	O*	-	Q*	-	1700

Lucis S24.L2.T12 CHARON LED / LDC (Polar)

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 16,2 W

Température Couleur: 4000 K

Module luminous flux: 2564 lm

Luminaire luminous flux: 1764 lm

A: 280 mm

B: 240 mm

C: 125 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 1700 g

Luminaire: Lucis S24.L2.T12 CHARON LED
Lamps: 1 x LED G6

