



CHARON S29.L2.T135.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate

Could be combined with metal ring in white, chrome, brass or stainless steel.



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Motion sensor | Emergency module | Bluetooth | Track system | Weight |
|------|------|-------------------------|----------------------------|-----|-----|-----|--------|---------------|------------------|-----------|--------------|--------|
| 21,3 | 4000 | 3476 | 2400 | 360 | 290 | 130 | M | O* | P* | Q* | - | 2800 |

Lucis S29.L2.T135 CHARON LED / LDC (Polar)

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 21,3 W

Color temperature: 4000 K

Module luminous flux: 3476 lm

Luminaire luminous flux: 2400 lm

A: 360 mm

B: 290 mm

C: 130 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 2800 g

Luminaire: Lucis S29.L2.T135 CHARON LED
Lamps: 1 x LED G6

