

POLARIS ZT ZT.P2.500.XY


Type: suspension lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: rod

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Bluetooth	Emergency module	Weight		
37,3	4000	6096	5486	500	1000	M	-	P*	Q*	R*	-	8100

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 37,3 W

Color temperature: 4000 K

Module luminous flux: 6096 lm

Luminaire luminous flux: 5486 lm

A: 500 mm

C: 1000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 8100 g

Lucis ZT.P2.500.X POLARIS ZT LED / LDC (Polar)

Luminaire: Lucis ZT.P2.500.X POLARIS ZT LED
Lamps: 1 x LED G6

