

POLARIS ZK PE ZK.P2.400.XY PE


Type: suspension lamp

Lampshade: polyethylene opal PE

Metal parts: painted steel plate RAL 9003 (.31), RAL 9005 (.61), RAL chrom (.77), chrome (.80), stainless steel (.83) or brass (.84)

Pendant: white or black self-carrying conductor reinforced with a steel wire

The luminaire driver is placed right inside the luminaire (LED version).



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	C	DALI 2	Motion sensor	Bluetooth	Track system	Weight		
25,5	4000	4096	3769	400	2000	M	-	P*	Q*	-	D*	4200

Lucis ZK.P2.400.X PE POLARIS ZK PE LED / LDC (Polar)

Voltage: 230V

Ballast: Driver

IK code: IK10

CRI: >90

LED life: L80/F10 50000 hours

Watt: 25,5 W

Color temperature: 4000 K

Module luminous flux: 4096 lm

Luminaire luminous flux: 3769 lm

A: 400 mm

C: 2000 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Available on inquiry

Weight: 4200 g

Luminaire: Lucis ZK.P2.400.X PE POLARIS ZK PE LED
Lamps: 1 x LED G6

