

POLARIS ZL PE ZL1.P2.400.XY PE

Type: luminaire suspendu

Abat-jour: polyéthylène opal PE

Les pièces métalliques: acier laqué RAL 9003 (.31), RAL chrom (.77) ou chromé (.80)

Suspension: câbles d'acier avec câble transparent

The luminaire driver is placed right inside the luminaire (LED version).



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | C | DALI 2 | ☼ | ☼ | 📶 | 📄 | 👤 | |
|------|------|-------------------------------|----------------------------------|-----|------|-----------|---|----|----|----|---|------|
| 25,5 | 4000 | 4096 | 3769 | 400 | 2000 | M | - | P* | Q* | R* | - | 4100 |

Tension: 230V

Ballaste: Driver

IK code: IK10

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 25,5 W

Température Couleur: 4000 K

Module luminous flux: 4096 lm

Luminaire luminous flux: 3769 lm

A: 400 mm

C: 2000 mm

Dali 2: Disponible

Capteur de mouvement: Non disponible

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Disponible sur demande

Sádrokarton: Non disponible

Poids: 4100 g

Lucis ZL1.P2.400.X PE POLARIS ZL PE LED / LDC (Polar)

Luminaire: Lucis ZL1.P2.400.X PE POLARIS ZL PE LED
Lamps: 1 x LED G6

