




CHARON PMMA S26.L4.CA2.Y

Typ: Decken- und Wandleuchte

Lampenschirm: Acrylglas PMMA

Leuchte: weiß lackiertes Stahlblech



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	Emergency	Exit	Bluetooth	Track	Weight
10,7	4000	1738	1243	300	260	115	M	O*	-	Q*	-	1200

Spannung: 230V

IK Code: IK06

Vorschalgerät: Driver

CRI: >90

LED-Lebensdauer: L80/F10 50000 Stunden

Watt: 10,7 W

Farbtemperatur: 4000 K

Module luminous flux: 1738 lm

Luminaire luminous flux: 1243 lm

A: 300 mm

B: 260 mm

C: 115 mm

Dali 2: Verfügbar

Bewegungsmelder: Verfügbar auf Anfrage

Notlichtmodul: Nicht Verfügbar

Bluetooth-Steuerung: Verfügbar auf Anfrage

Track-System: Nicht Verfügbar

Sádrokarton: Nicht Verfügbar

Gewicht: 1200 g

Lucis S26.L4.CA2 CHARON PMMA LED / LDC (Polar)

Luminaire: Lucis S26.L4.CA2 CHARON PMMA LED
Lamps: 1 x LED G6

