



CHARON PMMA S44.L5.CA4.Y

Type: luminaire de plafond et mural

Abat-jour: verre acrylique PMMA

Luminaire: tôle en acier peint en blanc



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Emergency | Bluetooth | Track system | Weight |
|------|------|-------------------------------|----------------------------------|-----|-----|-----|-----------|-----------|-----------|--------------|----------|
| 26,7 | 3000 | 4020 | 2785 | 480 | 440 | 160 | M | O* | P* | Q* | - - 2600 |

Lucis S44.L5.CA4 CHARON PMMA LED / LDC (Polar)

Tension: 230V

IK code: IK06

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 26,7 W

Température Couleur: 3000 K

Module luminous flux: 4020 lm

Luminaire luminous flux: 2785 lm

A: 480 mm

B: 440 mm

C: 160 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Disponible sur demande

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 2600 g

Luminaire: Lucis S44.L5.CA4 CHARON PMMA LED
Lamps: 1 x LED G6

