

CHARON S24.L3.T12.Y

Type: luminaire de plafond et mural

Abat-jour: verre blanc, soufflé de manière artisanale, à trois couches, satin opale mat

Luminaire: tôle en acier peint en blanc

Could be combined with metal ring in white, chrome, brass or stainless steel.



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | DALI 2 | Emergency | Bluetooth | Track system | Weight | |
|------|------|-------------------------------|----------------------------------|-----|-----|-----|-----------|-----------|-----------|--------------|--------|------|
| 10,7 | 3000 | 1608 | 1092 | 280 | 240 | 125 | M | O* | - | Q* | - | 1700 |

Lucis S24.L3.T12 CHARON LED / LDC (Polar)

Tension: 230V

IK code: IK01

Ballaste: Driver

CRI: >90

La vie de LED: L80/F10 50000 heures

Watt: 10,7 W

Température Couleur: 3000 K

Module luminous flux: 1608 lm

Luminaire luminous flux: 1092 lm

A: 280 mm

B: 240 mm

C: 125 mm

Dali 2: Disponible

Capteur de mouvement: Disponible sur demande

Module d'urgence: Non disponible

Contrôle Bluetooth: Disponible sur demande

Track system: Non disponible

Sádrokarton: Non disponible

Poids: 1700 g

Luminaire: Lucis S24.L3.T12 CHARON LED
Lamps: 1 x LED G6

