




**DAPHNE ZT ZT.L1.D450.XY**

**Type:** suspension lamp

**Lampshade:** white, hand-blown, three-layered glass, satin opal matt

**Pendant:** white painted steel RAL 9003 (.31), chrome (.80), brass (.84), RAL chrom (.77) or RAL Argento dorato (.70) rod suspension



W	K	Module luminous flux lm	Luminaire luminous flux lm	A	B	C	DALI 2	IK	IP	Bluetooth	Emergency	Weight
32	3000	4824	3570	450	200	1000	M	-	P*	Q*	R*	5400

Lucis ZT.L1.D450.X DAPHNE LED / LDC (Polar)

**Voltage:** 230V

**IK code:** IK01

**Ballast:** Driver

**CRI:** >90

**LED life:** L80/F10 50000 hours

**Watt:** 32 W

**Color temperature:** 3000 K

**Module luminous flux:** 4824 lm

**Luminaire luminous flux:** 3570 lm

**A:** 450 mm

**B:** 200 mm

**C:** 1000 mm

**Dali 2:** Available

**Motion sensor:** Not available

**Emergency module:** Available on inquiry

**Bluetooth control:** Available on inquiry

**Track system:** Available on inquiry

**Sádrokarton:** Not available

**Weight:** 5400 g

Luminaire: Lucis ZT.L1.D450.X DAPHNE LED  
Lamps: 1 x LED G6

