


IZAR III ZLI3.L1.900.XY

Type: suspension lamp

Lampshade: acrylic glass, front white (.92) or black (.93)

Metal parts: white painted steel plate

Pendant: steel wire suspension with a transparent cable



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | ☺ | ☺ | ☺ | ☺ | ☺ | ☺ |
|------|------|-------------------------|----------------------------|-----|----|------|----|--------|---|----|----|----|---|------|
| 30,7 | 3000 | 4047 | 3712 | 900 | 80 | 2000 | 40 | M | - | P* | Q* | R* | - | 2700 |

Lucis ZLI3.L1.900.X IZAR III LED / LDC (Polar)

Voltage: 230V

IK code: IK06

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 30,7 W

Color temperature: 3000 K

Module luminous flux: 4047 lm

Luminaire luminous flux: 3712 lm

A: 900 mm

B: 80 mm

C: 2000 mm

D: 40 mm

Dali 2: Available

Motion sensor: Not available

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Available on inquiry

Sádrokarton: Not available

Weight: 2700 g

Luminaire: Lucis ZLI3.L1.900.X IZAR III LED
Lamps: 1 x LED G6

