



ZERO IP44 PS13.K4.Z500.Y

Type: ceiling and wall lamp

Lampshade: white, hand-blown, three-layered glass, satin opal matt

Light body: white painted steel plate



| W | K | Module luminous flux lm | Luminaire luminous flux lm | A | B | C | D | DALI 2 | ☺ | ☺ | ☺ | ☺ | ☺ | ☺ | ☺ |
|----|------|-------------------------|----------------------------|-----|-----|----|----|--------|----|----|----|---|---|---|------|
| 29 | 4000 | 4133 | 3225 | 500 | 450 | 90 | 13 | M | O* | P* | Q* | - | - | - | 5900 |

Voltage: 230V

IK code: IK01

Ballast: Driver

CRI: >90

LED life: L80/F10 50000 hours

Watt: 29 W

Color temperature: 4000 K

Module luminous flux: 4133 lm

Luminaire luminous flux: 3225 lm

A: 500 mm

B: 450 mm

C: 90 mm

D: 13 mm

Dali 2: Available

Motion sensor: Available on inquiry

Emergency module: Available on inquiry

Bluetooth control: Available on inquiry

Track system: Not available

Sádrokarton: Not available

Weight: 5900 g

Lucis PS13.K4.Z500 ZERO LED / LDC (Polar)

Luminaire: Lucis PS13.K4.Z500 ZERO LED
Lamps: 1 x LED G5

